

COMMISSION OF THE EUROPEAN COMMUNITIES

COM(82) 702 final

Brussels, 3 November 1982

Draft of

COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs
Tariff duties on certain industrial products

(submitted to the Council by the Commission)

COM

COM(82) 702 final

EXPLANATORY MEMORANDUM

1. The subject of the following draft regulation is the temporary suspension of duties in the Common Customs Tariff for a number of industrial items, as requested by the Member States.
It is partly a prolongation and partly a new measure.

2. It seems appropriate to the Commission that a duty suspension is justified for the goods listed in the annex to this regulation. The Commission proposes a total suspension for those products for which Community production does not exist or is minimal. A partial suspension is proposed in cases where the Community production covers only a part of the requirements. The rate of the partially suspended duty depends on the extent of the possible Community supply to the Community users. The Commission is also always looking for the right balance between the interests of the suppliers, users and the consumers in the Community. It also takes into account the need to protect employment.

3. The proposed measures are confined to six months because of the difficulties of estimating the evolution of the basic factors.

4. For a number of items for which the Member States also requested duty suspensions the Commission does not propose a tariff measure because the necessary conditions are not fulfilled. This concerns the following items :

Common Customs Tariff heading No	Description
ex 28.04 C III	Tellurium
ex 29.13 E	2,4-Dihydroxybenzophenone (4-Benzoylresorcinol)
ex 29.14 C	Methyl 3-(2,2-dichlorovinyl)-2,2-dimethyl- cyclopropane carboxylate
ex 29.22 D I	3,5-Dichloroaniline with a purity of not less than 99 % by weight
ex 29.22 E II	3,3'-Dichlorobenzidine dihydrochloride
ex 29.25 B III b)	<u>N</u> -Acetylsulphanilyl chloride
ex 29.25 B III b)	<u>N</u> -4-Hydroxyphenylstearamide
ex 29.27	Isophthalonitrile
ex 29.29	2,4,6-Trichlorophenylhydrazine
ex 29.34 C	Dimethyl methylphosphonate
ex 29.35 Q	Isonicotinonitrile
ex 29.36	4,4'-Oxydi(benzenesulphonohydrazide)
ex 30.01 B II	Bile extract containing not less than 45%, by weight, of cholic acid
ex 30.03 A II b)	Cisplatin (INN)
ex 37.08	Powder preparation consisting of particles of magnetic iron oxide compounded with resin, wax and carbon black having a diameter of not less than 14 and not more than 15 micro- metres

Common Customs Tariff heading No	Description
ex 38.08 C	Rosin hydrogenated, polymerized, dimerized or oxidized
ex 38.19 X	Ivermectin (INN) dissolved in toluene
ex 39.01 C III a)	Reflecting self-adhesive sheeting made up of more than one layer of polyester, metallized, whether or not in rolls
ex 39.01 C III a)	Reflecting or partially reflecting films, tinted in the mass or metallised, containing substances opaque to ultra-violet rays, made up of two layers of polyethylene terephthalate glued to each other and a film of polypropylene glued on one surface, whether or not in rolls
ex 39.01 C III a)	Films tinted in the mass containing substances opaque to ultra-violet rays, made up of two layers of polyethylene terephthalate glued together, whether or not in rolls
ex 39.01 C III a)	Poly(ethylene terephthalate) film coated on one side with aluminium and a photoconductive layer

Common Customs Tariff heading No	Description
ex 39.02 C X	Copolymer of vinyl chloride and vinyl acetate containing not less than 85% and not more than 86.5% by weight of vinyl chloride and not less than 13.5% and not more than 15% by weight of vinyl acetate and with a residual content of vinyl chloride monomer of not more than 0.1 ppm and of which 50 grammes mixed with 150 grammes of doubly distilled water and stirred for 2 hours at room temperature gives, after filtration, a solution of which the surface tension is not less than 71.5 dynes/cm when measured at 23°C
ex 39.02 C XIV a)	Copolymer of vinyl chloride and vinyl acetate modified by maleic acid, containing not less than 85% and not more than 88% by weight of vinyl chloride, not less than 10.8% and not more than 14.2% by weight of vinyl acetate and not less than 0.8% and not more than 1.2% by weight of maleic acid and with a residual content of vinyl chloride monomer of not more than 0.1 ppm and of which 50 grammes mixed with 150 grammes of doubly distilled water and stirred for two hours at room temperature, gives after filtration, a solution of which the surface tension is not less than 71.5 dynes/cm when measured at 23°C
ex 39.02 C XIV a)	Poly(1-isobutylethylene) (Methylpentene polymer)
ex 39.02 C XIV b)	Polyethylene terephthalate tape covered on one side by aluminium foil on which there is a photoconductive layer consisting of resins, dyes and zinc oxide or other photoconductors
ex 40.11 A	Cushion tyres having a diameter not greater than 300 mm
ex 48.01 F	Paper bleached or unbleached treated with the ammonium salt of a fluorinated phosphate ester

Common Customs Tariff heading No	Description
ex 48.07 C	Bleached paper impregnated with acrylic resin and coated with poly(vinylidene chloride) having a thickness of not less than 200 and not more than 255 micrometres and of a weight per square metre of not less than 165 and not more than 180 grams
ex 48.07 D	Coloured paper impregnated with acrylic resin and coated with poly(vinylidene chloride) having a thickness of not less than 200 and not more than 255 micrometres and of a weight per square metre of not less than 165 and not more than 180 grams
ex 58.01 B	Carpets, carpeting and rugs, of silk or of waste silk other than noil, of which the pile contains not less than 85 % by weight of silk or waste silk other than noil (b)
ex 70.12 B	Glass flasks for vacuum vessels, of glass dyed in the mass, having a capillary tip at the base
ex 70.20 A	Mats of non-textile glass fibres of a weight per square metre of not more than 100 grams and a fibre diameter of not more than seven micrometres
ex 70.20 B	Yarns, spun from continuous glass filaments having a diameter of not less than 5.8 and not more than 6.4 micrometres of 33 or 34 tex or a multiple thereof and containing not more than 0.8% by weight of dressing
ex 70.20 B	Textured single yarns obtained from continuous glass filaments, having a diameter of not less than 5.2 micrometres and of not more than 6.2 micrometres
ex 70.20 B	Yarns of not less than 340 tex and not more than 680 tex obtained from continuous spun glass filaments having a diameter of not less than 12.5 micrometres and not more than 13.5 micrometres, with resorcinol-formaldehyde treated
ex 85.01 B I b)	D.C. electric motor with an output of 4 watts, an operating voltage of 12 volts, a maximum absorbed current under no-load conditions of 160 mA, self centring bushes, contained in a cylindrical casing whose diameter does not exceed 30 mm and connected to a tachometric dynamo having a capacity of 2 400 revolutions/minute

Common Customs Tariff heading No	Description
ex 85.21 D II	<p>Random access memories (RAMS) with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 24 mm with 18 connecting pins, and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2164 IMS 2620 3764 4164 4416 4864 M 58764 F 64 K 6642 6664 6665 8164 8264 8265</p> <p>or</p> <p>— other identification markings relating to RAMS complying with the above-mentioned description</p>
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS), with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>M 120 2101 8101 21 H 01 8102 2102 8111 21 L 02 9101 2111 91 L 01 21 H 11 9102 2112 91 L 02 21 H 12 9111 2115 91 L 11 21 L 15 9112 2125 91 L 12 21 L 25</p> <p>TMM 313 6810 68 A 10 68 B 10</p> <p>or</p> <p>— other identification markings relating to N-MOS Static RAMS complying with the abovementioned descriptions</p>

Common Customs Tariff heading No	Description
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS), with a storage capacity of 2 K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with 24 connecting pins or not more than 32 contact areas and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p style="margin-left: 40px;">MCM 2016 TMM 2016 2128 3528 TMS 4016 4802 58725 8128</p> <p>or</p> <p>— other identification markings relating to N-MOS Static RAMS complying with the abovementioned description</p>
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS), with a storage capacity of 16 K × 1 bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with 20 or 24 connecting pins or contact areas and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p style="margin-left: 40px;">2167 IMS 1400 58757 8167</p> <p>or</p> <p>— other identification markings relating to N-MOS Static RAMS complying with the above description</p>
ex 85.21 D II	<p>Dynamic random access memories, operating from a single + 5 V power supply, of N-MOS technology (N-MOS Dynamic single + 5 V power supply RAMS) with a storage capacity of 16 K-bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 × 24 mm, with no more than 16 connecting pins, and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or including one of those combinations:</p> <p style="margin-left: 40px;">2118 4517 4816 5295</p> <p>or</p> <p style="text-align: right;">N-MOS dynamic RAMS</p> <p>— other identification markings relating to / complying with the above-mentioned description</p>

Common Customs Tariff heading No	Description
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS) with a storage capacity of 1 K X 4 bits and an access time of not more than 85 ns, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 24 mm, with not more than 20 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2148 H 2149 H</p> <p>or</p> <p>N-MOS static RAMS</p> <p>— other identification markings relating to / complying with the abovementioned description</p>

Common Customs Tariff heading No	Description														
ex 85.21 D II	<p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than 2 timers each with a capacity of not more than 16 bits an internal clock, a read only memory (ROM) with a capacity of not less than 8 K-bits and not more than 32 K-bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K-bits, with less than 13 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm, with not more than 40 connecting pins and bearing:</p>														
	<p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p>														
	<table><tbody><tr><td>TMP 80 C 22</td><td>8020</td></tr><tr><td>- 80 C 48</td><td>8021 H</td></tr><tr><td>- 80 C 49</td><td>8022 H</td></tr><tr><td>- 80 C 50</td><td>8048</td></tr><tr><td>- 80 C 51</td><td>8049</td></tr><tr><td></td><td>8050</td></tr><tr><td></td><td>8051</td></tr></tbody></table>	TMP 80 C 22	8020	- 80 C 48	8021 H	- 80 C 49	8022 H	- 80 C 50	8048	- 80 C 51	8049		8050		8051
TMP 80 C 22	8020														
- 80 C 48	8021 H														
- 80 C 49	8022 H														
- 80 C 50	8048														
- 80 C 51	8049														
	8050														
	8051														
	<p>or</p>														
	<p>single-chip microcomputers</p>														
	<p>— other identification markings relating to / complying with the above-mentioned description</p>														
ex 85.21 D II	<p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than 2 timers each with a capacity of not more than 16 bits, an internal clock, and a random access memory (RAM) with storage capacity of not less than 512 bits and not more than 4 K-bits, with not less than 27 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm, with not more than 40 connecting pins and bearing:</p>														
	<p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p>														
	<table><tbody><tr><td>80 C 31</td><td>8031</td></tr><tr><td>80 C 35</td><td>8035</td></tr><tr><td>80 C 39</td><td>8039</td></tr><tr><td>80 C 40</td><td>8040</td></tr></tbody></table>	80 C 31	8031	80 C 35	8035	80 C 39	8039	80 C 40	8040						
80 C 31	8031														
80 C 35	8035														
80 C 39	8039														
80 C 40	8040														
	<p>or</p>														
	<p>single-chip microcomputers</p>														
	<p>— other identification markings relating to / complying with the abovementioned description</p>														

Common Customs Tariff heading No	Description
ex 85.21 D II	<p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than 2 timers each with a capacity of not more than 16 bits, an internal clock, an electronic programmable read only memory (EPROM) UV erasable with a storage capacity of not less than 8 k-bits and not more than 32 K-bits and a random access memory (RAM) with a storage capacity of not less than 512 bits and not more than 4 K-bits, with not less than 13 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm, with not more than 40 connecting pins, with a quartz window on the upper surface and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>68701 68705 8741 A 8748 8749 8750 8751</p> <p>or</p> <p>single-chip microcomputers</p> <p>— other identification markings relating to / complying with the abovementioned description</p>
ex 85.21 D II	<p>Gate Arrays : Logic array produced by means of Shottky-TTL technology with a maximum of 540 NAND functions, the number of inputs and outputs varying from a minimum of 28 to a maximum of 78, in the form of a monolithic integrated circuit in a package whose maximum dimensions are 25 x 83 mm with 24 to 68 connecting pins. Reference number - B 500 and TAT 004 or other numbers corresponding to circuits of the type described above</p>

Common Customs Tariff heading No	Description
ex 85.21 D II	Enhanced programmable communications interface (EPCI) in the form of a monolithic integrated circuit contained in a housing whose external dimensions do not exceed 37 x 15 mm with not more than 28 connecting pins, and bearing the following identification marking - 2661 - 3 N or other identification markings relating to EPCI devices as described above
ex 85.21 D II	Electronic control circuit for floppy discs, using N-MOS technology in the form of a monolithic integrated circuit contained in a 40 pin package with maximum dimensions of 53 x 14 mm. The package bears the reference number 8272 or another reference number corresponding to an FDC with the characteristics described above
ex 85.21 D II	Non-erasable read-only memory of N-MOS technology (N-MOS ^{static} -ROM), with a storage capacity of 64 Kbits in the form of a monolithic integrated circuit contained in a housing whose external dimensions do not exceed 32 x 14 mm with not more than 24 connecting pins and bearing the following identification marking 2364 or other identification markings relating to N-MOS Static ROM as described above
ex 85.21 D II	Logic array of bipolar components - Schottky (S), low power Schottky (LS), advanced Schottky (AS) and advanced low power Schottky (ALS) technologies, contained in a housing with not less than 20 and not more than 84 connecting pins, whose exterior dimensions are not less than 8 x 8 mm and not more than 19 x 19 mm with pins on all four sides. Reference number : SN/SNJ 54-74 S/LS/AS/ALS 000-1999 FC/FD or other identification markings corresponding to a logic array with the above characteristics

Common Customs Tariff heading No	Description
ex 85.21 D II	<p>Programmable logic array (PLA) - bipolar technology using a matrix of elementary functions of the AND/OR/NAND/NORINVERTER/FLIP-FLOP type, contained in an 8 x 25 mm - 16 x 32 mm package with one of the following reference numbers :</p> <p>FP54/74 ALS 16L8 (OR8 OR6 OR4) 20 pins FP54/74 LS 333 (0335) 24-pins FP54/74 AS 839 (0840) 24-pins</p> <p>or other reference numbers corresponding to PLAs as described above</p>
ex 85.21 D II	<p>Linear image sensor consisting of not less than 128 and not more than 3456 photosensitive areas, transfer gate, shift registers, reference elements, amplifiers and clocks, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 16 x 46 mm, with a glass window on the upper surface and with not more than 24 connecting pins and bearing :</p> <ul style="list-style-type: none">- one of the following identification markings : TC 101, TC 102, TC 103, TC 104- or other identification markings relating to linear image sensors complying with the above-mentioned description
ex 85.21 D II	<p>Logic array of bipolar components manufactured according to the following technologies ALS (advanced low power Shottky) and AS (advanced Shottky) in the form of monolithic integrated circuits in a package with dimensions between 20 x 8 mm and 40 x 16 mm with one of the following reference numbers :</p> <p>74 ALS.....N/J 54 ALS..... N/J 74 AS.....N/J 54 AS..... N/J</p> <p>or other reference numbers corresponding to logic arrays as described above</p>
ex 85.21 D II	<p>Gate arrays - standard and C-MOS technologies - employing between 200 and 10 000 elementary functions of the inverter/or/and/nand types; contained in a package with 24, 28, 40, 48, 64, 68, 84 or 128 pins with minimum dimensions of 170 x 20 mm. The integrated circuit may have a minimum of 11 input-and output-gates, and a maximum of 63 input and</p>

Common Customs Tariff heading No	Description																								
ex 85.21 D II (cont.d)	<p>63 output-gates. The packages are indicated with one of the following reference numbers:</p> <table data-bbox="674 448 1160 694"><tr><td>TAT 004</td><td>STL</td><td>technology</td></tr><tr><td>TAT 008</td><td>"</td><td>"</td></tr><tr><td>TAT 010</td><td>"</td><td>"</td></tr><tr><td>TAT 020</td><td>"</td><td>"</td></tr><tr><td>TAC 010</td><td>C</td><td>MOS technology</td></tr><tr><td>TAC 020</td><td>"</td><td>"</td></tr><tr><td>TAL 002</td><td>LS</td><td>technology</td></tr><tr><td>TAL 004</td><td>"</td><td>"</td></tr></table> <p>or other identification markings for Gate Arrays of the above-mentioned description</p>	TAT 004	STL	technology	TAT 008	"	"	TAT 010	"	"	TAT 020	"	"	TAC 010	C	MOS technology	TAC 020	"	"	TAL 002	LS	technology	TAL 004	"	"
TAT 004	STL	technology																							
TAT 008	"	"																							
TAT 010	"	"																							
TAT 020	"	"																							
TAC 010	C	MOS technology																							
TAC 020	"	"																							
TAL 002	LS	technology																							
TAL 004	"	"																							
ex 85.22 C II	<p>Electromagnetic display, with a write-time of 200 microseconds per segment, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide indefinite memory, 7 pivoting light reflecting segments each of which is attached to a bar magnet. The display is contained in a housing whose dimensions do not exceed 50 x 28 x 36 mm</p>																								
ex 90.28 A II b)	<p>Microprocessor controlled centrifugal analyser having an exchangeable rotor and longitudinal cuvettes and a spectrophotometer with xenon flash</p>																								
ex 92.12 A	<p>Prelubricated hard disks for storage peripherals - Winchester technology - with high storage capacity (non-formatted memory) to 21.7 Mbits, external diameter 130 mm</p>																								

5. Attention is drawn to the fact that the Council Resolution of 27.6.1974 simplifying the task of the customs administrations (O.J. C 79/80) requires the publication of the attached Regulation at least six weeks before its entry into force.

DRAFT OF A
COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs Tariff duties on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the draft Regulation submitted by the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries of the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

From 1 January to 30 June 1983 the autonomous Common Customs Tariff duties for the products listed in the Annex hereto shall be suspended at the level indicated in respect of each of them.

Article 2

This Regulation shall enter into force on 1 January 1983.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 1982.

For the Council
The President

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 13.03 A V	Extract of dewaxed pyrethrum	0
ex 27.07 A I	Crude light oils containing by weight : - not less than 10% of vinyltoluenes - not less than 10% of indene - not less than 1% and not more than 5% of naphthalene	0
ex 28.14 B	Iodine pentafluoride	0
ex 28.55 A	Phosphides of iron (ferro-phosphorus) containing by weight: — Not less than 68 % and not more than 72 % of iron, — Not less than 22 % and not more than 26 % of phosphorus, — Not more than 3.5 % of silicon, of which not less than 99 % by weight is of a particle size of less than 20 micrometres, for the manufacture of varnishes or paints (a)	0
ex 29.01 D VII	1,3-Diisopropylbenzene with a purity of not less than 94 % by weight	0
ex 29.08 A III c)	2-Bromo-6-methoxynaphthalene	0
ex 29.16 A II	<u>L</u> -Malic acid and its salts	0
ex 29.16 D	Methyl 5-(2,4-dichlorophenoxy)-2-nitrobenzoate	0
ex 29.21 B II	<u>O,O</u> -Dioctadecyl pentaerythritol bis(phosphite)	0
ex 29.21 B II	1,1-Dimethyl-2,2'-oxydiethylene tetraphenyl bis(phosphite)	0
ex 29.22 A III	1,1-Dimethylprop-2-ynylamine	5
ex 29.22 D VII	<u>N</u> -(1-Ethylpropyl)-2,6 dinitro-3,4-xylidine	7
ex 29.25 B III b)	3,5-Dichloro- <u>N</u> -(1,1-dimethylprop-2-ynyl)benzamide	0
ex 29.31 B	Probucol (INN)	0
ex 29.31 B	Ethoprophos (ISO)	0
ex 29.35 Q	<u>L</u> -Tryptophan	0
ex 29.35 Q	2-Chloro-5-trifluoromethylpyridine	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	Alprazolam (INN)	4.5
ex 29.44 C	Aclarubicine hydrochloride (INN)	0
ex 29.44 C	Mitomycin (INN)	0
ex 30.03 B II b)	Purified collagen dispersed in a phosphate buffered physiological saline solution containing not less than 0.1% and not more than 0.5% of lidocaine (INN) by weight	6.3
ex 37.02 B	Colour negative film of a width not less than 75 mm and not more than 105 mm and of a length of 100 m or more, for use in the manufacture of instant picture film packs (a)	0
ex 38.03 B	Acid activated montmorillonite which, when examined by X-ray powder diffraction, shows four principal lines corresponding to crystal interplane spacing (d values) of 0.44, 0.40, 0.33 and 0.25 nm the line corresponding to 0.40 nm being the most intense, for the manufacture of self-copy paper (a)	0
ex 38.19 G	Catalysts, in the form of rodlets, having a diameter of not less than 1.5 mm and not more than 9.5 mm, containing not less than 60 % by weight of diiron trioxide, not less than 8 % by weight of dipotassium oxide and not less than 0.5 % by weight of dichromium trioxide	0
ex 38.19 G	Catalysts, in the form of granules or rings, having a diameter of not less than 3 mm and more than 10 mm, consisting of silver supported on aluminium oxide, the silver content being not less than 10 % and not more than 20 % by weight	0
ex 38.19 G	Catalysts consisting of a mixture of oxides on a silicon dioxide support and containing by weight: (a) Not less than 25 % and not more than 40 % of antimony (b) Not less than 5 % and not more than 10 % of iron (c) Not less than 0.2 % and not more than 1.5 % of molybdenum (d) Not less than 0.8 % and not more than 4.0 % of tellurium	0
ex 38.19 G	Catalyst in the form of granules having a diameter of not more than 1.4 mm, consisting of cobalt oxide on a silicon dioxide support	0
ex 38.19 G	Catalysts consisting of dichromium trioxide, fixed on a silicon dioxide support, with a pore volume, as determined by nitrogen absorption method, of not less than 2 cm ³ /g	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 38.19 X	Grains, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight not less than 70 % and not more than 78 % dialuminium trioxide and not less than 19 % and not more than 26 % zirconium dioxide	6.4
ex 38.19 X	Grains, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight not less than 54 % and not more than 62 % dialuminium trioxide and not less than 36 % and not more than 44 % zirconium dioxide	6.4
ex 38.19 X	Cholic acid and 3- <i>alpha</i> , 12- <i>alpha</i> -dihydroxy-5- <i>beta</i> -cholan-24-oic acid (deoxycholic-acid), crude	0
ex 38.19 X	Crude bile acids	0
ex 38.19 X	Reaction products of dibutyl dihydrogendiphosphate and 1,2-epoxypropane	0
ex 38.19 X	A mixture of 5-ethyl-2-methyl-2-oxo-1,3,2 Λ^5 -dioxaphosphan-5-ylmethyl methyl phosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2 Λ^5 -dioxaphosphan-5-ylmethyl) methylphosphanate	0
ex 39.01 C III a)	Reflecting polyester sheeting in which glass microspheres are embedded, whether or not in rolls	0
ex 39.01 C III a)	Transparent film, consisting of polyester coated with a layer of indium and silver	0
ex 39.01 C V	Reflecting polyurethane sheeting, whether or not in rolls	0
ex 39.02 C I a)	Polyethylene, in one of the forms mentioned in Note 3 (b) to Chapter 39, having a density of not less than 0.954 and not more than 0.958 grams per cubic centimetre, for the manufacture of typewriter ribbon or similar ribbon (a)	
ex 39.02 C VI a)	Copolymer of maleic anhydride and styrene, whether or not containing a styrene-butadiene block copolymer in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C VI b)	Plates made of a copolymer consisting of maleic anhydride and styrene, also containing styrene-block copolymer, covered on both sides with a sheet of the abovementioned copolymer, modified with butadiene or pigmented	0
ex 39.02 C VII b)	Reflecting polyvinyl chloride sheeting, wholly embossed on one side in a regular pyramidal pattern, whether or not in rolls	0
ex 39.02 C XIV a)	Copolymer of tetrafluorethylene and hexafluorpropylene compounded with materials which are opaque to X-rays and containing not less than 15 % and not more than 30 % by weight of such materials	0
ex 39.02 C XIV a)	Terpolymer of ethylene, methyl acrylate and a monomer containing a non-terminal carboxy group as a substituent, compounded with silica	12.5

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 39.02 C XIV a)	Copolymer of acrylonitrile and methylacrylate modified with polybutadiene-acrylonitrile (NBR)	0
ex 39.02 C XIV a)	Ionomer resin consisting of a salt of a copolymer of ethylene and methacrylic acid	0
ex 39.02 C XIV a)	Ionomer resin consisting of a salt of a terpolymer of ethylene, isobutyl acrylate, and methacrylic acid	0
ex 39.07 B V d)	Reflecting tape of a width not exceeding 105 mm consisting of a facing strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat sealed, in parallel lines or a grid pattern to a backing strip of plastic material, or of knitted or woven fabric covered on one side with plastic material, whether or not on rolls	0
ex 51.01 A	Yarn of poly(<i>p</i> -phenyleneterephthalamide), for uses other than the manufacture of tyres or of products used in the manufacture of tyres (a)	2
ex 51.01 A	Non-textured filament yarn of poly(vinyl alcohol) for the manufacture of sleeves for printing rollers(a)	0
ex 56.01 A and ex 59.01 B I	Fibres of poly(<i>p</i> -phenyleneterephthalamide)	2
ex 56.01 A	Textile fibres exclusively of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, for uses other than the manufacture of articles falling within Chapters 60, 61, 64 and 65 or of materials used in the manufacture of such articles (a)	0
ex 56.01 A	Textile fibres containing not less than 85 % by weight of fibres of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid and not less than 1 % and not more than 15 % by weight of fibres of poly(<i>p</i> -phenyleneterephthalamide)	6
ex 56.01 A	Acetalised, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion polymerised poly(vinyl alcohol) and vinyl=chloride	0
ex 59.03	Bonded fibre fabrics and similar bonded yarn fabrics of aromatic polyamide man-made fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, whether or not impregnated or coated, in the piece or cut into rectangles	0
ex 59.03	Bonded-fibre fabrics, with a thickness of not more than 300 micrometres of spunbonded poly=ethylene fibres, with a weight not exceeding 115 g/m ² , whether or not impregnated or coated, in the piece or cut into rectangles	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 59.03	Poly(vinyl alcohol) bonded fibre fabrics, with a thickness of not less than 200 micrometres and not more than 280 micrometres and of a weight of not less than 20 g/m ² and not more than 50 g/m ² , whether or not impregnated or coated, in the piece or cut into rectangles	0
ex 59.08	Knitted or woven fabric coated or covered on one side with artificial plastic material in which are embedded glass microspheres	0
ex 70.20 A	Non-textile glass fibres having a diameter of less than 4 micrometres	0
ex 70.20 B	Spun roving of not less than 7 000 tex with a core of not less than 600 tex and not more than 1 500 tex, made from continuous glass fibre, coated with epoxy resin	5
ex 81.04 G I	Electrolytic manganese of a purity of at least 99.7 % by weight, for the production of non-ferrous alloys (a)	0
ex 84.51 A	Typewriters with Braille characters	0
ex 84.51 A	Electronic pocket communicators for handicapped persons which, by means of push buttons and printing thermic head, print and issue text on tape	0
ex 84.51 A	Portable machine for reading and writing Braille with tactile read-out and magnetic tape cassette recording systems, microphone and speaker, equipped with a standard electro-mechanical Braille typewriter keyboard and an electro-mechanical Braille read-out unit with 20 characters, all contained in a case measuring 24 × 36 × 11 cm	0
ex 84.55 C	Parts and accessories of electronic pocket communicators for handicapped persons which, by means of push buttons and printing thermic head, print and issue text on tape	0
ex 84.55 C	Opto-electric encoder for electronic typewriters consisting of electronic circuits, a light-emitting diode (LED), a rotating disc with radial openings, a fixed mask and a single chip photovoltaic cell, contained in two plastic shells forming a housing of a size not exceeding 60 × 48 × 16 mm	0
ex 84.55 C	Winchester technology magnetic heads for disk file peripherals, capable of recording to a density of 35.4 tracks per mm	0
ex 85.03	Dry zinc/carbon batteries of a voltage of not less than 5.5 and not more than 6.5 and of a size not exceeding 110 × 90 × 5 mm, for incorporation in film cassettes for instant pictures (a)	0
ex 85.19 B	Potentiometers, for use as volume control, contained in a housing whose diameter does not exceed 4.5 mm, whether or not fitted with an on/off switch, for the manufacture of appliances falling within tariff subheading 90.19 B I (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 A V	Colour cathode-ray tubes, using shadow mask, in-line technology in which images are displayed on a screen with a useable surface not exceeding 165 × 165 mm for use in electronic flight instrument, warning and systems displays (a)	0
ex 85.21 A V	Digital displays in the form of a tube consisting of a glass housing mounted on a board whose dimensions do not exceed 350 × 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metalized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 85.21 D II	Digital displays of a size not exceeding 25 × 35 mm, consisting of a printed circuit board on which are mounted, under a transparent plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semi-conductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots	0
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 × 90 mm, with a single line of characters, not less than two in number, comprising light-emitting diodes made from gallium-based semi-conductor compounds mounted thereon. Each character is composed of up to eight segments and the line of characters has a protective cover of transparent plastic	0
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 × 90 mm, with a single line of digits, not less than three in number, comprising light-emitting diodes manufactured from gallium-based semi-conductor compounds mounted thereon. Each digit is composed of seven segments plus a decimal point and the line of digits has a protective cover of transparent plastic	0
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS) of Schottky TTL technology, with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 9 × 23 mm, with 16 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>14 S 10 24 S 10 24 SA 10 247 A 10 27 S 20 27 S 21 29760 29761 38510 5300 5301 53 S 140 53 S 141 54 S 287</p>	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty(%)
ex 85.21 D II (cont'd)	54 S 387 54700 5603 5623 6300 6301 63 S 140 63 S 141 7052 7057 74 S 287 74 S 387 7610 7611 82 S 126 82 S 129 8520 8521 93417 93427 or — other identification markings relating to PROMS complying with the abovementioned description	11.5

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS) of Schottky TTL technology, with a storage capacity of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>27 S 12 27 S 13 28 L 22 28 LA 22 29613 29770 29771 38510 5305 5306 5308 5309 53 S 240 53 S 241 54 S 570 54 S 571 5604 5624 6305 6306 6308 6309 63 S 240 63 S 241 6335 6336 7053 7058 74 S 570 74 S 571 76 LS 03 7620 7621 82 S 114 82 S 130 82 S 131 93436 93446</p> <p>or</p> <p>— other identification markings relating to PROMS complying with the abovementioned description</p>	11.5

Common Customs Tariff heading No	Description		Rate of autonomous duty (%)
ex 85.21 D II	Programmable, non-erasable, read only memories (PROMS), with a storage capacity of 4 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins, and bearing:		
	— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:		
	18 S 42	3604	7121
	18 S 46	3624	7122
	18 SA 42	3625	7123
	18 SA 46		7125
			7126
		38510	
	24 S 41		
	24 SA 41	5340	74 S 472
		5341	74 S 473
		53S440	74 S 474
	27 S 15	53RA441	74 S 475
	27 S 26	53RS441	74 S 476
	27 S 27		74 S 477
	27 S 28	53S441	74 S 572
	27 S 29	5348	74 S 573
	27 S 30	5349	
	27 S 31	5350	
	27 S 32	5351	7640
	27 S 33	5352	7641
		5353	7642
			7643
			7644
	28 L 42		7644
	28 L 45	54 S 472	7645
	28 P 42	54 S 473	7647
	28 P 45	54 S 474	7648
	28 R 45	54 S 475	7649
		54 S 476	
		54 S 477	
	28 SA 41	54 S 572	82 HS 137
	28 S 42	54 S 573	82 HS 147
	28 SA 42	54740	
	28 S 45	54741	
	28 S 46		82 S 115
	28 SA 46		82 S 136
		5605	82 S 137
		5625	82 S 140
	29620		82 S 141
	29621		82 S 142
	29622	6340	82 S 146
	29623	6341	82 S 147
	29624	63S440	
	29625	63RA441	
	29626	63RS441	93438
	29627	63S441	93448
		6348	93452
		6349	93453
		6350	
		6351	
		6352	
		6353	
		HM 6641	
		7054	
		7059	
	or		
	— other identification markings relating to PROMS complying with the abovementioned description		

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)																																																						
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS), with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins or not more than 28 contact areas, and bearing :</p>																																																							
	<p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p>																																																							
	<table border="0"> <tr><td>24 S 81</td><td>6380</td><td>82707</td></tr> <tr><td>24 SA 81</td><td>6381</td><td>82708</td></tr> <tr><td>24 S 86</td><td>6388</td><td>82 LS 180</td></tr> <tr><td></td><td>6389</td><td>82 LS 181</td></tr> <tr><td></td><td></td><td>82 S 180</td></tr> <tr><td>27 S 180</td><td>63S840</td><td>82 S 181</td></tr> <tr><td>27 S 181</td><td>63S841</td><td>82 S 182</td></tr> <tr><td></td><td></td><td>82 S 183</td></tr> <tr><td></td><td></td><td>82 S 184</td></tr> <tr><td>28 L 85</td><td>7050</td><td>82 S 185</td></tr> <tr><td>28 L 86</td><td></td><td>82 S 2708</td></tr> <tr><td>28 P 85</td><td></td><td>87 S 180</td></tr> <tr><td>28 R 85</td><td>7127</td><td>87 S 181</td></tr> <tr><td>28 S 2708</td><td>7128</td><td>87 S 184</td></tr> <tr><td>28 S 85</td><td>7129</td><td>87 S 185</td></tr> <tr><td>28 S 86</td><td>7130</td><td>87 S 186</td></tr> <tr><td>28 SA 86</td><td>7131</td><td>87 S 187</td></tr> <tr><td></td><td>7132</td><td></td></tr> </table>	24 S 81	6380	82707	24 SA 81	6381	82708	24 S 86	6388	82 LS 180		6389	82 LS 181			82 S 180	27 S 180	63S840	82 S 181	27 S 181	63S841	82 S 182			82 S 183			82 S 184	28 L 85	7050	82 S 185	28 L 86		82 S 2708	28 P 85		87 S 180	28 R 85	7127	87 S 181	28 S 2708	7128	87 S 184	28 S 85	7129	87 S 185	28 S 86	7130	87 S 186	28 SA 86	7131	87 S 187		7132		
24 S 81	6380	82707																																																						
24 SA 81	6381	82708																																																						
24 S 86	6388	82 LS 180																																																						
	6389	82 LS 181																																																						
		82 S 180																																																						
27 S 180	63S840	82 S 181																																																						
27 S 181	63S841	82 S 182																																																						
		82 S 183																																																						
		82 S 184																																																						
28 L 85	7050	82 S 185																																																						
28 L 86		82 S 2708																																																						
28 P 85		87 S 180																																																						
28 R 85	7127	87 S 181																																																						
28 S 2708	7128	87 S 184																																																						
28 S 85	7129	87 S 185																																																						
28 S 86	7130	87 S 186																																																						
28 SA 86	7131	87 S 187																																																						
	7132																																																							
	<table border="0"> <tr><td>29623</td><td></td><td>93450</td></tr> <tr><td>29630</td><td>74 LS 478</td><td>93451</td></tr> <tr><td>29631</td><td>74 S 2708</td><td>93460</td></tr> <tr><td>29632</td><td>74 S 454</td><td>93461</td></tr> <tr><td>29633</td><td>74 S 455</td><td>93465</td></tr> <tr><td>29634</td><td>74 S 478</td><td>93466</td></tr> <tr><td>29635</td><td>74 S 479</td><td>93 L 450</td></tr> <tr><td>29636</td><td></td><td>93 L 451</td></tr> <tr><td>29637</td><td></td><td></td></tr> <tr><td>29650</td><td>7608</td><td></td></tr> <tr><td>29651</td><td>7680</td><td>9460</td></tr> <tr><td>29652</td><td>7681</td><td></td></tr> <tr><td>29653</td><td>7684</td><td></td></tr> <tr><td></td><td>7685</td><td></td></tr> <tr><td></td><td>7686</td><td></td></tr> <tr><td>3628</td><td>7687</td><td></td></tr> <tr><td></td><td>7688</td><td></td></tr> <tr><td></td><td>7689</td><td></td></tr> </table>	29623		93450	29630	74 LS 478	93451	29631	74 S 2708	93460	29632	74 S 454	93461	29633	74 S 455	93465	29634	74 S 478	93466	29635	74 S 479	93 L 450	29636		93 L 451	29637			29650	7608		29651	7680	9460	29652	7681		29653	7684			7685			7686		3628	7687			7688			7689		
29623		93450																																																						
29630	74 LS 478	93451																																																						
29631	74 S 2708	93460																																																						
29632	74 S 454	93461																																																						
29633	74 S 455	93465																																																						
29634	74 S 478	93466																																																						
29635	74 S 479	93 L 450																																																						
29636		93 L 451																																																						
29637																																																								
29650	7608																																																							
29651	7680	9460																																																						
29652	7681																																																							
29653	7684																																																							
	7685																																																							
	7686																																																							
3628	7687																																																							
	7688																																																							
	7689																																																							
	<table border="0"> <tr><td>5380</td><td></td><td></td></tr> <tr><td>5381</td><td></td><td></td></tr> <tr><td>5388</td><td>77 S 180</td><td></td></tr> <tr><td>5389</td><td>77 S 181</td><td></td></tr> <tr><td></td><td>77 S 184</td><td></td></tr> <tr><td>53S840</td><td>77 S 185</td><td></td></tr> <tr><td>53S841</td><td>77 S 186</td><td></td></tr> <tr><td></td><td>77 S 187</td><td></td></tr> </table>	5380			5381			5388	77 S 180		5389	77 S 181			77 S 184		53S840	77 S 185		53S841	77 S 186			77 S 187																																
5380																																																								
5381																																																								
5388	77 S 180																																																							
5389	77 S 181																																																							
	77 S 184																																																							
53S840	77 S 185																																																							
53S841	77 S 186																																																							
	77 S 187																																																							
	<table border="0"> <tr><td>54 LS 478</td><td></td><td></td></tr> <tr><td>54 S 2708</td><td></td><td></td></tr> <tr><td>54 S 454</td><td></td><td></td></tr> <tr><td>54 S 455</td><td>TBPS 81 M</td><td></td></tr> <tr><td>54 S 478</td><td></td><td></td></tr> <tr><td>54 S 479</td><td></td><td></td></tr> </table>	54 LS 478			54 S 2708			54 S 454			54 S 455	TBPS 81 M		54 S 478			54 S 479																																							
54 LS 478																																																								
54 S 2708																																																								
54 S 454																																																								
54 S 455	TBPS 81 M																																																							
54 S 478																																																								
54 S 479																																																								
	or																																																							
	<p>other identification markings relating to PROMS complying with the abovementioned description</p>																																																							

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)																																								
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS), with a storage capacity 16K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins or not more than 28 contact areas, and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <table data-bbox="545 539 863 1025"> <tr><td>TBP 28 L 166</td><td>HM 76 16-5</td></tr> <tr><td>TBP 28 P 166</td><td>DM 77 S 190</td></tr> <tr><td>TBP 28 R 166</td><td>DM 77 S 191</td></tr> <tr><td>TBP 28 S 166</td><td>MM 82 S 190</td></tr> <tr><td>29681</td><td>SM 82 S 190</td></tr> <tr><td>29681 A</td><td>S 82 S 190</td></tr> <tr><td>29683</td><td>MM 82 S 191</td></tr> <tr><td>29683 A</td><td>SM 82 S 191</td></tr> <tr><td>3636</td><td>N 82 S 191</td></tr> <tr><td>3636-1</td><td>S 82 S 191</td></tr> <tr><td>M 36 36</td><td>DM 87 S 190</td></tr> <tr><td>53S1641</td><td>DM 87 S 191</td></tr> <tr><td>53LS1681</td><td>93 510 C</td></tr> <tr><td>53PS1681</td><td>93 510 M</td></tr> <tr><td>53S1681</td><td>93 511 C</td></tr> <tr><td>53S1681</td><td>93 511 M</td></tr> <tr><td>63S1641</td><td></td></tr> <tr><td>63LS1681</td><td></td></tr> <tr><td>63PS1681</td><td></td></tr> <tr><td>63S1681</td><td></td></tr> </table> <p>7134 7136 7138 HM 76 160-2 HM 76 160-5 HM 76 161-2 HM 76 161-5 HM 76 16-2</p> <p>or</p> <p>— other identification marking relating to PROMS complying with the above-mentioned description</p>	TBP 28 L 166	HM 76 16-5	TBP 28 P 166	DM 77 S 190	TBP 28 R 166	DM 77 S 191	TBP 28 S 166	MM 82 S 190	29681	SM 82 S 190	29681 A	S 82 S 190	29683	MM 82 S 191	29683 A	SM 82 S 191	3636	N 82 S 191	3636-1	S 82 S 191	M 36 36	DM 87 S 190	53S1641	DM 87 S 191	53LS1681	93 510 C	53PS1681	93 510 M	53S1681	93 511 C	53S1681	93 511 M	63S1641		63LS1681		63PS1681		63S1681		
TBP 28 L 166	HM 76 16-5																																									
TBP 28 P 166	DM 77 S 190																																									
TBP 28 R 166	DM 77 S 191																																									
TBP 28 S 166	MM 82 S 190																																									
29681	SM 82 S 190																																									
29681 A	S 82 S 190																																									
29683	MM 82 S 191																																									
29683 A	SM 82 S 191																																									
3636	N 82 S 191																																									
3636-1	S 82 S 191																																									
M 36 36	DM 87 S 190																																									
53S1641	DM 87 S 191																																									
53LS1681	93 510 C																																									
53PS1681	93 510 M																																									
53S1681	93 511 C																																									
53S1681	93 511 M																																									
63S1641																																										
63LS1681																																										
63PS1681																																										
63S1681																																										

Common Customs Tariff heading No	Description	Rate of auto- nomous duty(%)
ex 85.21 D II	<p>Electronic programmable ready only memories (EPROMS) UV erasable, with a storage capacity of 2 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with a quartz window on the upper surface, and bearing :</p> <p>— an identification marking either consisting of one of the following combinations of figures and letters or including one of those combinations:</p> <p>B 1702 A AMI 702 ADC 82140 PP</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Electronic, programmable, read only memories (EPROMS) UV erasable, with a storage capacity of 32 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with a quartz window on the upper surface, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2532 68732 25 A 32 68 L 732 25 L 32 2732</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	8.5
ex 85.21 D II	<p>Electronic, programmable, read only memories (EPROMS) UV erasable, with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with a quartz window on the upper surface, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2564 2764</p> <p>68 L 64 68764 68 A 764 68 L 764 68766</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	8.5

Common Customs Tariff heading No	Description	Rate of autonomous duty(%)
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS), with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>4008 4118 PD 421 4801</p> <p>8104 8108 8112 8114 8185</p> <p>or</p> <p>— other identification markings relating to N-MOS Static RAMS complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Static random access memories of C-MOS technology (C-MOS Static RAMS) with a storage capacity of 64 K-bits in the form of a monolithic integrated circuit in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 28 connecting pins and bearing :</p> <p>— an identification marking consisting of the following combination of figures and letters or including this combination;</p> <p>TC 5564</p> <p>or</p> <p>— other identification markings relating to C-MOS static RAMS / complying with the abovementioned description</p>	0

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)																						
ex 85.21 D II	<p>Random access memories of emitter coupled logic technology (ECL RAMS), with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 11 × 31 mm, with 20 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p style="padding-left: 40px;">F 10480 100480</p> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to ECL RAMS complying with the abovementioned description</p>	0																						
ex 85.21 D II	<p>Static random access memory of TTL technology (TTL SRAM), with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 30 mm, with not more than 22 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <table style="margin-left: 40px; border: none;"> <tr><td>2205</td><td>93412</td></tr> <tr><td>2510</td><td>93 L 412</td></tr> <tr><td>2511</td><td>93415</td></tr> <tr><td>74 LS 214</td><td>93 L 415</td></tr> <tr><td>74 LS 215</td><td>93422</td></tr> <tr><td>74 LS 314</td><td>93 L 422</td></tr> <tr><td>74 LS 315</td><td>93425</td></tr> <tr><td>74 S 207</td><td>93 F 425</td></tr> <tr><td>74 S 208</td><td>93 L 425</td></tr> <tr><td>74 S 214</td><td></td></tr> <tr><td>74 S 314</td><td></td></tr> </table> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to TTL Static RAMS complying with the abovementioned description</p>	2205	93412	2510	93 L 412	2511	93415	74 LS 214	93 L 415	74 LS 215	93422	74 LS 314	93 L 422	74 LS 315	93425	74 S 207	93 F 425	74 S 208	93 L 425	74 S 214		74 S 314		0
2205	93412																							
2510	93 L 412																							
2511	93415																							
74 LS 214	93 L 415																							
74 LS 215	93422																							
74 LS 314	93 L 422																							
74 LS 315	93425																							
74 S 207	93 F 425																							
74 S 208	93 L 425																							
74 S 214																								
74 S 314																								
ex 85.21 D II	<p>Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 4 bits plus a read only memory (ROM) with a capacity of not less than 18 K bits and not more than 65 K bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits, contained in a housing whose exterior dimensions do not exceed 16 × 54 mm, with not more than 40 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures and letters or including one of those combinations:</p> <table style="margin-left: 40px; border: none;"> <tr><td>CD 3200 to 3299</td><td>TMC 1980 to 1999</td></tr> <tr><td>TMC 0270 to 0279</td><td>TP 0310 to 0329</td></tr> <tr><td>TMC 0500 to 0599</td><td>TP 0450 to 0459</td></tr> <tr><td>TMC 0980 to 0989</td><td>TP 0480 to 0489</td></tr> <tr><td>TMC 1500 to 1599</td><td>TP 0500 to 0599</td></tr> </table> <p style="padding-left: 40px;">or</p> <p style="padding-left: 100px;">single-chip</p> <p>— other identification markings relating to microcomputers complying with the abovementioned description</p>	CD 3200 to 3299	TMC 1980 to 1999	TMC 0270 to 0279	TP 0310 to 0329	TMC 0500 to 0599	TP 0450 to 0459	TMC 0980 to 0989	TP 0480 to 0489	TMC 1500 to 1599	TP 0500 to 0599	0												
CD 3200 to 3299	TMC 1980 to 1999																							
TMC 0270 to 0279	TP 0310 to 0329																							
TMC 0500 to 0599	TP 0450 to 0459																							
TMC 0980 to 0989	TP 0480 to 0489																							
TMC 1500 to 1599	TP 0500 to 0599																							

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 8 bits, a 12 bit timer, an internal clock, a read only memory (ROM) with a capacity of 32 K bits and a random access memory (RAM) with a capacity of 1 K bit, with 48 input/output gates and contained in a housing whose exterior dimensions do not exceed 16.5 × 42 mm, with 64 connecting pins, and bearing:</p> <p>— an identification marking either consisting of the following combination of figures and letters or including this combination:</p> <p style="padding-left: 40px;">PD 7801</p> <p style="padding-left: 40px;">or</p> <p style="padding-left: 120px;">single-chip</p> <p>— other identification markings relating to microcomputers complying with the abovementioned description</p>	10
ex 85.21 D II	<p>P-MOS 12/24-hour clock circuit, incorporating an elapsed time facility, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 53 × 14 mm, with 40 connecting pins, for the manufacture of instrument panel clocks and clocks of a similar type for vehicles (a), and bearing:</p> <p style="text-align: right; padding-right: 20px;">motor</p> <p>— an identification marking either consisting of the following combination of figures and letters or including this combination:</p> <p style="padding-left: 40px;">MM 53124</p> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to clock circuits complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Monolithic integrated circuit, consisting of eight independent elements capable of controlling the eight segments and/or characters of fluorescent or gas discharge displays, contained in a housing whose exterior dimensions do not exceed 7 × 23 mm, with 18 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or including one of those combinations:</p> <p style="padding-left: 40px;">513 514 534 594 6118 6128 6138</p> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to circuits complying with the abovementioned description</p>	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Programmable, non-erasable, logic circuit (Field Programmable Logic Array) of TTL Schottky technology, with 48 AND functions and eight OR functions and 16 inputs, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with 28 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>82 S 100 82 S 101 93458 93459</p> <p>or</p> <p>— other identification markings relating to programmable logic arrays complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Programmable, non-erasable, logic circuit (Field Programmable Gate Array) of bipolar technology, in the form of a monolithic integrated circuit with AND/NAND functions, containing 16 inputs and nine outputs, contained in a housing whose dimensions do not exceed 17 × 39 mm, with 28 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>82 S 102 82 S 103</p> <p>or</p> <p>— other identification markings relating to programmable gate arrays complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Arithmetic-logic unit of H-MOS technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, one 24 bit register, one 4 bit register, twelve 1 bit registers, two 16 × 24 bit service memories, one logic network performing arithmetic and logic operations, decodifying logic, an error detection and management logic, one 8 bit counter, and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <p>— the identification marking ALU 0486</p> <p>or</p> <p>— other identification markings relating to arithmetic-logic units complying with the abovementioned description</p>	0

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Sequence control circuit of H-MOS technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, three 16 bit registers, one 16 × 16 bit service memory, one 7 × 17 bit last in first out (LIFO) memory, one adder circuit, decodifying logic, priority logic, error detection and management logic, one 16 bit multiplexer, one 8 bit counter and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <p>— the identification marking CSS 0484</p> <p>or</p> <p>— other identification markings relating to sequence control circuits complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Logic control circuit of H-MOS technology in the form of a monolithic integrated circuit consisting of one 7 bit register, three timers, one multiplexer, sequential and combining networks intended to perform control operations, decodifying logic, error detection and management logic and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <p>— the identification marking MIC 0482</p> <p>or</p> <p>— other identification markings relating to logic control circuits complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Amplifier, in the form of a monolithic integrated analog circuit, contained in a housing whose dimensions do not exceed 3.56 × 3.56 × 1.65 mm, with not more than 10 connecting pins, for use in products falling within subheading 90.19 B I a), and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>V 35 C 05</p> <p>or</p> <p>— other identification markings relating to amplifiers complying with the abovementioned description</p>	0
ex 85.21 D II	<p>C-MOS clock circuits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 54 x 16mm, with not more than 42 connecting pins, for the production of automatic time-switches, instrument panel clocks and clocks of a similar type for motor vehicles (a).</p> <p>The case bears :</p> <p>- an identification marking either consisting one of the following combinations of figures and letters or including one of those combinations:</p> <p>HI 2060 HI 2065 T 3605</p> <p>or</p> <p>- other identification marking relating to clock circuits complying with the above mentioned description</p>	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Direct Access Memory controllers of N-MOS technology (N-MOS DMA Controller) in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 14 x 53 mm with not more than 40 connecting pins, and bearing:</p> <p>- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations :</p> <p>AM 9517A 8237</p> <p>or</p> <p>- other identification markings relating to N-MOS DMA controllers complying with the abovementioned description</p>	11.5
ex 90.01 A	Octagonal Fresnel lens of acrylic resin unmounted, for use in overhead projectors (a)	0
ex 90.19 A III	Vascular prostheses of which the largest opening has an internal diameter not exceeding 8 mm	0
ex 90.19 A III	Vascular prostheses of which the largest opening has an internal diameter exceeding 8 mm	4
ex 90.19 A III	Artificial heart valves	0
ex 90.19 B I	Receivers for hearing aids, contained in a housing whose external dimensions, excluding connecting points, do not exceed 6.5 x 4.5 x 3.2 mm	0
ex 90.19 B II	Reading appliances for the blind, in which a miniature camera using photo-transistors transmits letters onto a scanning board with piezo-electric pencils, and their parts and accessories	0
ex 90.20	Apparatus for the irradiation of biological samples incorporating permanently shielded caesium 137 radioactive sources, an exposure chamber whose volume does not exceed 930 cubic centimetres, an electrically driven turntable and a digital timer	0
ex 98.04 A II	Non-fibrous plastic pen-tips with an internal channel	0
	Flint wheels, whether or not with guard wheels, for use in the manufacture of non-refillable gas-fuelled pocket lighters (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.